

MetroCount Traffic Executive Exploración De los Datos

ExpIDat-39 -- español (ESN)

Datasets:

Sitio: [East] Farmer Fwy Tunnel East Ln1 <80kph>
Dirección: 2 - Dirección este, A pulsó primero., **Carril:** 1
Duración Del Examen: 1:59 sábado, 27 de abril de 2002 => 10:43 viernes, 03 de mayo de 2002
Archivo: E:\Demo Data\Farmer Fwy\East03May2002.EC1 (Demo FB)
Identificador: 250421ZQ MC56-6 [MC55] (c)Microcom 02/03/01
Algoritmo: Factory default
Tipo de datos: Sensores de eje - apareados (clase, velocidad, cuenta)

Perfil:

Tiempo del filtro: 2:00 sábado, 27 de abril de 2002 => 10:00 viernes, 03 de mayo de 2002
Clases incluidas: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12
Gama de la velocidad: 5 - 160 km/h.
Dirección: Del norte, Del este, Sur, Del oeste (Limitar)
Separación: Todos - (Progreso)
Nombre: Factory default profile
Esquema: Clasificación del vehículo (AustRoads94)
Unidades: Métrico (metro, kilómetro, m/s, km/h, kilogramo, tonelada)

Validation Parameters

Fail if no data (State = TRUE)
 Fail if bad direction code (State = TRUE)
 Fail if bad sensor layout (State = TRUE)
 Maximum percent sensor mismatch (Limit = 2%)
 Maximum number of failures displayed (300)
 Number in time step to permit validation (10)
 Time step in minutes (60)
 Maximum number of consecutive empty steps (6)
 Failed steps required to signal (4)
 Maximum percent rejected hits (Limit = 15%)
 Minimum percent passenger automobiles (Limit = 30%)
 Maximum percent unclassifiable (Limit = 7%)
 Class maximum percent (2, Limit = 100%)
 Class maximum percent (8, Limit = 20%)
 Class maximum percent (10, Limit = 20%)
 Percent vehicles less than threshold speed (7,2 km/h, Limit = 7%)
 Percent vehicles more than threshold speed (118,8 km/h, Limit = 10%)
 Percent vehicles with correlation less than threshold (0, Limit = 20%)
 Percent vehicles with separation less than threshold (0, Limit = 20%)

Pass/Fail scan

Start Pre-Scan...
 Pre-Scan OK

Start Data Scan...
 Data Scan OK

Start Post-Scan...
 Post-Scan OK

Final Result - Pass