

MetroCount Traffic Executive Balayage De Données

DataScan-39 -- français (FRA)

Ensembles de données:

Emplacement: [East] Farmer Fwy Tunnel East Ln1 <80kph>
Direction: 2 - Vers l'est, A a frappé d'abord., **Voie:** 1
Durée D'Aperçu: 01:59 samedi 27 avril 2002 => 10:43 vendredi 3 mai 2002
Fichier: E:\Demo Data\Farmer Fwy\East03May2002.EC1 (Demo FB)
Marque: 250421ZQ MC56-6 [MC55] (c)Microcom 02/03/01
Algorithme: Factory default
Type de données: Sondes d'axe - appareillées (classe, vitesse, compte)

Profil:

Temps de filtre: 02:00 samedi 27 avril 2002 => 10:00 vendredi 3 mai 2002
Classes incluses: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12
Étendue de vitesse: 5 - 160 km/h.
Direction: Nord, Est, Sud, Ouest (vers)
Séparation: Tous - (Progrès)
Nom: Factory default profile
Arrangement: Classification de véhicule (AustRoads94)
Unités: Métrique (mètre, kilomètre, m/s, km/h, kilogramme, tonne)

Validation Parameters

Fail if no data (State = TRUE)
 Fail if bad direction code (State = TRUE)
 Fail if bad sensor layout (State = TRUE)
 Maximum percent sensor mismatch (Limit = 2%)
 Maximum number of failures displayed (300)
 Number in time step to permit validation (10)
 Time step in minutes (60)
 Maximum number of consecutive empty steps (6)
 Failed steps required to signal (4)
 Maximum percent rejected hits (Limit = 15%)
 Minimum percent passenger automobiles (Limit = 30%)
 Maximum percent unclassifiable (Limit = 7%)
 Class maximum percent (2, Limit = 100%)
 Class maximum percent (8, Limit = 20%)
 Class maximum percent (10, Limit = 20%)
 Percent vehicles less than threshold speed (7,2 km/h, Limit = 7%)
 Percent vehicles more than threshold speed (118,8 km/h, Limit = 10%)
 Percent vehicles with correlation less than threshold (0, Limit = 20%)
 Percent vehicles with separation less than threshold (0, Limit = 20%)

Pass/Fail scan

Start Pre-Scan...
 Pre-Scan OK

Start Data Scan...
 Data Scan OK

Start Post-Scan...
 Post-Scan OK

Final Result - Pass